

“V-WING” T-8 HIGH BAY

T-8 high-bay fixture incorporates a highly efficient “V-Wing” design for locations where a wide, even distribution of light is required. The fixture is lightweight but sturdy, with features that make mounting and maintenance simple. This fixture is an excellent replacement for low and high bay High Pressure Sodium and Metal Halide fixture. The fixture is available in 4 different lamp configurations to allow for various light levels.

FEATURES

- Factory pre-assembled and pre-wired, install lamps (and any optional accessories) and mount!
- “Fast Connect” plug connector on back of fixture attaches quickly to power cord provided with fixture. Allows for quick installation & easy maintenance.
- 7/8” Knockout in each end for hardwire installation
- Multi-Volt Ballast 120-277 or 347-480 (GE or Sylvania)
- 10’ 600v ST cord with plug standard
- Zinc coated 6-gauge V-hangers provided standard
- 2 lamp fixture is designed to replace a 70-100w HID
- 3 lamp fixture is designed to replace a 15-175w HID
- 4 lamp fixture is designed to replace a 250w HID
- 6 lamp fixture is designed to replace 400w HID



6-Lamp Fixture—Replaces 400w HID 1 for 1

SPECIFICATIONS

- Housing: Painted, 20 gauge steel (NYC approved)
- Reflector: 95% reflective MIRO 4™
- Electrical: GE or Sylvania electronic ballast
- Labels: UL Listed as fluorescent fixture suitable for dry or damp locations
- Optional Wireguard is 11 gauge zinc coated steel
- Optional Lens is .125 prismatic
- System Wattages (with watt-miser T5 lamp):

Fixture:	120-volt	277-volt
2-lamp:	73 watts	74 watts
3-lamp:	111 watts	109 watts
4-lamp:	148 watt	145 watts
6-lamp:	221 watts	215 watts

- “STEP” AND “VARIABLE” DIMMING BALLASTS AVAILABLE!
- The “Step” dimmable ballasts steps the light output from 100% to 60%.
- The “Variable” dimming ballast can dim from 100% to 60% and anywhere in between.
- Wattage for a 6 lamp fixture can drop from 215 watts to 132 watts!



4-lamp fixture shown with wire guard & sensor

OPTIONS

- Motion Sensor
- Wire Guard
- White reflector
- Custom Cord Length

Fixture Order Code: **VW4 6 T8 EB N – (OPTIONS)**



132 McCarrell Ln.
Zelienople, PA 16063
(724) 453-1201

Fixture Series	Qty Lamps 2, 3, 4 or 6	Lamp Type	Ballast Code EB = Normal S= Step Dim V = Var Dim	Voltage N = 120 to 277 H = 347 to 480	Options: WG = Wireguard WREF= White Reflector OS = Sensor CCL = Custom Cord Length (specify length ex: CCL12)
----------------	------------------------------	-----------	---	---	--

WWW.LIGHTWINGSLIGHTING.COM